

In(A) S(mm ²)	6	10	16	25	32	40	50	63	80	100	125								In(A) S(mm ²)
1,5	99	60	37	24	19	15	12	9	7	6	5								1,5
2,5	166	99	62	40	31	25	20	16	12	10	8								2,5
4	265	159	99	64	50	40	32	25	20	16	13								4
6	397	238	149	95	75	60	48	38	30	24	19								6
10		397	248	159	124	99	79	63	50	40	32								10
16			397	254	199	159	127	101	79	64	51								16
25				397	311	248	199	158	124	99	79								25
35						348	278	221	174	139	111								35
50 ⁽¹⁾							378	300	236	189	151								50 ⁽¹⁾
70								442	348	278	223								70
95								599	472	378	302								95
120								757	596	477	382								120
150																			150
185																			185
240																			240
300																			300
400																			400
(1) Section théorique 47,5 ²		TABLEAU des LONGUEURS MAXIMALES AUTORISEES en Mètres									Type de protection		Tension d'alimentation		Conducteurs		N° du tableau		
											Disjoncteur Type "C"		U ₀ (Volts)		CUIVRE		L _{max} 321		
											Guide UTE C 15-105		230						

In(A) S(mm ²)	10	16	20	25	32	40	50	63	80	100	125	160	200	250	315	400	500	630	800	1000	In(A) S(mm ²)	
1,5	111	83	62	38 47	18 22	13 16	6 7															1,5
2,5		138	102	82	49 56	35 43	16 20	12 15	5 7													2,5
4		220		131	89	76	42 52	31 39	14 17	8 10	4 5	3 4										4
6		330			134	113	78	67	31 39	18 23	10 12	7 9	3 4									6
10		550			223	189	129	112	74	51 57	27 34	19 24	9 12	7 9	3 4							10
16		880			357		207	179	119	91	67	49 56	24 30	18 23	9 11	5 7	3 4					16
25		1376			558			279	186	143	104	88	59 61	45 53	22 27	13 16	7 9	4 5				25
35		1926			782				261	200	146	123	86	75	43 52	25 31	14 18	8 11	4 5			35
50 ⁽¹⁾		#####			#####					271	198	167	117	101	71	46 57	26 33	16 19	8 11	5 6		50 ⁽¹⁾
70											291	246	172	150	104	80	60	34 42	17 22	11 14		70
95												333	233	203	141	109	82	63	32 40	20 25		95
120													295	256	179	137	103	80	51 57	32 40		120
150														279	194	149	112	87	62	44 49		150
185															230	176	133	102	74	58		185
240																219	166	127	92	73		240
300																		153	110	87,2		300
	(1) Section théorique 47,5mm ²																					
TABLEAU des LONGUEURS MAXIMALES AUTORISEES en Mètres										Type de protection		Nature Isolation		Conducteurs		N° du tableau						
										FUSIBLES gG		PVC k = 115		CUIVRE		L _{max} 241						
										U ₀ = 230 Volts		PRC k = 143										